

GUIDE TO SELECTING FIRE EXTINGUISHERS

Model	Description	Nominal Capacity	Shipping Weight	Cylinder Dia.	Overall Height	Overall Width	Shipping Volume	U/L Rating	US CG Approved
Grenadier-P	The "water press" extinguisher contains water and compressed air. This unit is operated by simply squeezing the lever which opens the valve allowing the water to be forced out. It's especially effective on deep seated Class A fires. Units shipped empty. View Online.	2-1/2 gal.	7.75 lbs. «	7"	24-1/2"	9"	1.1 cu.ft.	2A	YES
Cosmic 2-1/2E*	These units contain specially fluidized and siliconized mono ammonium phosphate powder which smothers and breaks the chain reaction on Class B fires, fuses and insulates Class A fires, and is a non-conductor of electricity. Truly an all-purpose extinguisher, the ABC Dry Chemical is the most popular unit currently on the market. Non-toxic. View Online.	2-1/2 lbs.	5.5 lbs.	3-3/8"	15-1/2"	5-3/4"	.2 cu.ft.	1A-10BC	YES
Cosmic 5E		5 lbs.	10 lbs.	4-1/4"	16-3/8"	7-1/4"	.35 cu.ft.	3A-40BC	YES
Cosmic 6E		6 lbs.	12.75 lbs.	5"	16"	7-3/4"	.5 cu.ft.	3A-40BC	YES
Cosmic 10E		10 lbs.	18.25 lbs.	5-1/8"	21"	7-3/4"	.65 cu.ft.	4A-80BC	YES
Cosmic 20E (FE20C)		20 lbs.	33.5 lbs.	7-1/2"	21-1/4"	8-3/4"	1.0 cu.ft.	10A-120BC	YES
Cosmic 20E (FE20A)		20 lbs.	38 lbs.	7"	24"	10-1/4"	1.0 cu.ft.	6A-120BC	YES
495		50 lbs.	174 lbs.	--	46"	21-1/2"	--	20A-160BC	--
Sentinel 5	This extinguisher contains liquid carbon dioxide under pressure. The discharge, which changes into a gas and appears as a smothering cloud of white snow, is then directed to the fire through a funnel-shaped horn. The clean agent is particularly effective on small Class B fires and is a non-conductor of electricity. View Online.	5 lbs.	14 lbs.	5-1/4"	17-3/4"	8-1/4"	.65 cu.ft.	5BC	YES
Sentinel 10		10 lbs.	28.25 lbs.	7"	24"	12"	1.3 cu.ft.	10BC	YES
Sentinel 15		15 lbs.	37.75 lbs.	7"	30"	12"	1.0 cu.ft.	10BC	YES
Sentinel 20		20 lbs.	50.75 lbs.	8"	30"	13"	2.1 cu.ft.	10BC	YES
Galaxy 2-1/2E*	These models contain a siliconized sodium bicarbonate base, the traditional dry chemical. The Galaxy series can be an economical choice for Class B and Class C fire protection, due to generally lower recharging costs. Clean up after use is relatively easy because the chemical does not normally bake to a hot metal surface. Non-toxic. View Online.	2-1/2 lbs.	5/5 lbs.	3-3/8"	15-1/2"	5-3/4"	.2 cu.ft.	10BC	YES
Galaxy 5		5 lbs.	9.25 lbs.	4-1/4"	15-1/4"	5-1/2"	.35 cu.ft.	10BC	YES
Galaxy 5-1/2		5-1/2 lbs.	10.5 lbs.	4-1/4"	16-3/8"	7-1/4"	.4 cu.ft.	40BC	YES
Galaxy 6		6 lbs.	13.75 lbs.	5"	16-1/4"	8-1/2"	.5 cu.ft.	40BC	YES
Galaxy 10		10 lbs.	18.25 lbs.	5-1/8"	21"	7-3/4"	.65 cu.ft.	40BC or 60BC	YES
Galaxy 20		20 lbs.	38 lbs.	7-1/2"	23-1/4"	10-1/4"	1.0 cu.ft.	120BC	YES
496		50 lbs.	174 lbs.	--	46"	21-1/2"	--	160BC	--
Mercury 2-1/2*	This model contains the clean extinguishing agent Halotron © 1, which is EPA-approved, government-accepted and specified. This agent discharges as a liquid, then quickly evaporates leaving no residue to clean up afterwards. US FAA-approved for use in airports, NFPA-10 rating. Electrically non-conductive. View Online.	2-1/2 lbs	5.25 lbs	3-3/8"	15-1/2"	6-3/8"	.25 cu.ft.	2BC	N/A
Mercury 5		5 lbs	9.5 lbs	4-1/4"	16-3/8"	7-1/4"	.3 cu.ft.	5BC	YES
Mercury 11 (FM11C)		11 lbs	21.25 lbs	7"	17-1/2"	8-5/8"	1.0 cu.ft.	1A-10BC	YES
Mercury 11 (FM11A)		11 lbs	22.5 lbs	6"	21-7/8"	9-1/4"	1.0 cu.ft.	1A-10BC	YES
Mercury 15-1/2 (FM15C)		15-1/2 lbs	25.75 lbs	7"	17-1/2"	8-5/8"	1.0 cu.ft.	2A-10BC	YES
Mercury 15-1/2 (FM15A)	15-1/2 lbs	27.5 lbs	6"	21-7/8"	9-1/4"	1.0 cu.ft.	2A-10BC	YES	
Saturn 15	These units are ideal for commercial restaurant applications as a portable supplement to pre-engineered suppression systems. A low "pH" potassium acetate and potassium citrate solution is discharged in a fine mist that provides excellent range while cooling the fire and preventing splashing of liquid cooking media fires. View Online.	1.8 gal	22.5 lbs	7"	19-1/4"	9"	.9 cu.ft.	Class K	-
Saturn 25		2.5 gal	33.5 lbs.	7"	24-1/2"	9"	1.1 cu.ft.	Class K	-
272	This model dispenses water in a mist that is ideal for Class A fires and where a potential Class C (electrical) hazard exists. Non magnetic cylinder and misting nozzle. Units shipped empty. View Online.	2.5 gal	8 lbs. «	7"	28"	14"	1.3 cu ft.	2AC	--

* INDICATES MARK BRACKET STANDARD. J HOOK WALL BRACKET STANDARD WITH ALL OTHER EXTINGUISHERS.

«JL extinguishers are shipped fully charged with the exception of the Grenadier P & 272. **Note:** NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service For More Information About Ordering Tagged Extinguishers in Your Area. [OPEN SUBMITTAL DOCUMENT](#)