



AUTOMATIC FLUSH BOLTS



Automatic flush bolts are installed in the top and bottom of the inactive door. Closing the active door automatically extends both top and bottom bolts 3/4" into frame and sill strikes, locking in active door. Opening the active door retracts top and bottom bolts, releasing the inactive door.

Automatic Flush Bolts (UL Listed)			
QTY	#	FIRE-RATED METAL DOORS	ANSI/BHMA
	3142	Set of Top & Bottom Bolts - 3 Hour Fire Rating These non-handed bolts fit up to 8' x 9' metal doors. Fully Automatic. Patented free floating cams require a maximum of 5 lbs force on active door. Bolts can be vertically adjusted up to 1-1/2". Requires 2" clearance, overall length of each bolt is 12". Dust- proof strike optional. Wt: 2.4 lbs	156.3, Type 25
	3140	Single Top Bolt - 3 Hour Fire Rating When Used with Horizontally-Installed BFB This non-handed bolt fits up to 8' x 9' metal doors. Fully Automatic. Patented free floating cams require a maximum of 5 lbs force on active door. Bolts can be vertically adjusted up to 1-1/2". Requires 2" clearance, overall length of bolt is 12". When ordered with bottom fire bolt BFBM, (3140-BFBM) eliminates the need for bottom automatic flush bolt and dust-proof strike. Wt: 1.2 lb	156.3, Type 25
QTY	#	FIRE-RATED WOOD DOORS	ANSI/BHMA
	3242	Set of Top & Bottom Bolts - 1-1/2 Hour Fire Rating These non-handed bolts fit up to 8' x 9' wood doors. Fully Automatic. Patented free floating cams require a maximum of 5 lbs force on active door. Bolts can be vertically adjusted up to 1/2". Requires 2" clearance, overall length of each bolt is 8-1/2". Dust-proof strike optional. Wt: 2.9 lb	156.3, Type 25
	3240	Single Top Bolt - 1-1/2 Hour Fire Rating These non-handed bolts fit up to 8' x 9' wood doors. Fully Automatic. Patented free floating cams require a maximum of 5 lbs force on active door. Bolts can be vertically adjusted up to 1/2". Requires 2" clearance, overall length 8-1/2". When ordered with bottom fire bolt BFBW, (3240-BFBW) eliminates the need for bottom automatic flush bolt and dust-proof strike. Wt: 1.5 lb	156.3, Type 25
	3662	Set of Top & Bottom Bolts - 1-1/2 Hour Fire Rating These non-handed bolts fit up to 8' x 9' wood doors. Fully Automatic. Patented free floating cams require a maximum of 3 lbs force (ADA-compliant) on active door. Bolts can be vertically adjusted up to 1/2". Requires 2-1/4" clearance, overall length of each bolt is 5-3/4". Door Preparation: Only (2) 1-1/8" diameter holes are required. The top bolt is installed first and then the edge bolt. The edge bolt's grooved channel will engage the top bolt's grooved bottom, locking them together. Dust-proof strike optional. Wt: 2.9 lbs	156.3, Type 25
	3660	Single Top Bolt - 1-1/2 Hour Fire Rating These non-handed bolts fit up to 8' x 9' wood doors. Fully Automatic. Patented free floating cams require a maximum of 3 lbs force (ADA-compliant) on active door. Bolts can be vertically adjusted up to 1/2". Requires 2-1/4" clearance, overall length of each bolt is 5-3/4". Door Preparation: Only (2) 1-1/8" diameter holes are required. The top bolt is installed first and then the edge bolt. The edge bolt's grooved channel will engage the top bolt's grooved bottom, locking them together. When ordered with bottom fire bolt BFBW, (3660-BFBW), eliminates the need for bottom automatic flush bolt and dust-proof strike. Wt: 1.5 lb	156.3, Type 25
FIRE BOLTS, STRIKES & TRIM			
	BFBM	Bottom Fire Bolt, UL Listed to pairs of fire doors when specified with an automatic and self latching top flush bolt models 3140 or 3805. US32D. Bolt projects at 230°F, locking leaves. Wt: .1 lb	630
	BFBW	Bottom Fire Bolt, UL Listed to pairs of fire doors when specified with an automatic and self latching top flush bolt models 3240, 3905 or 3660. US32D. Bolt projects at 230°F, locking leaves. Wt: .1 lb	630
	380	Dust Proof Strike: 2" deep for floor installation. Face plate 1-1/2" x 3" in US32D or US32 finish. 2 fasteners #8 x 3/4" APA with Rawl plug. 1" x 2-1/8" prep hole for 3/4" bolt. Wt: .4 lb	156.16, L04021
	381	Dust Proof Strike: 2" deep for threshold installation. Std Finish US32D or US32. 1 Tru Arc ring fastener. 1" x 2-1/8" prep hole for 3/4" bolt. Wt: .4 lb	156.16, L04021
	382	Dust Proof Universal Strike: 2" deep for threshold or floor installation. US 3, 4,10, 10B, 26, 26D finishes available. Adjustable plate for carpet, threshold or concrete includes lock nut and screw package for all installations. 1" x 2" prep hole for 3/4" bolt. Wt: .1 lb	156.16, L04021
	-T	Flush Bolt Trim Package: US 3,4,10,10B, 26,26D, 32, 32D. Add "T" to Model Number.	



 	Distributor:	Quantity:
	Contractor:	Approved By:
	Model #: Finish:	Architect:
	Project:	Date:
HEADQUARTERS: 4450 WEST 78TH ST CIRCLE, BLOOMINGTON, MN 55435-5416 PH: 800-554-6077 FAX: 952-835-2218 EMAIL: JL@JLINDUSTRIES.COM WWW.ACTIVARCPG.COM 10/12/10		