

FIRE EXTINGUISHERS - COSMIC 5X MULTI PURPOSE DRY CHEMICAL - Portable Handheld

ABC dry chemical is a multipurpose extinguishing agent that is suitable for use in offices, classrooms, churches, parking garages and retail. Not recommended for use on sensitive electronic equipment.



CLASS A FIRES

Common
Combustibles



CLASS B FIRES

Flammable
Liquids
and Gases



CLASS C FIRES

Energized
Electrical
Equipment

SPECIFICATIONS:

These units contain specially fluidized and siliconized mono ammonium phosphate powder, which smothers and breaks the chain reaction on Class B fires, fuses and insulates Class A fires and is a non-conductor of electricity. Non-toxic.

Conforms to Test Standards: CAN/ULC-S504 — ANSI/UL299 & CAN/ULC S508 — ANSI/UL711

Operation: Squeeze the lever, which opens the valve, allowing the chemical to be forced out. Upright squeeze grip operation.

Temperature Range: -65° F (-53° C) to 120° F (49° C)

Construction: Heavy-duty steel cylinder with siphon tube, replaceable molded valve stem seal, visual pressure gauge, pull pin and upright squeeze grip. Corrosion and impact-resistant powder coat finish.

Valve Material: Aluminum

ADDITIONAL OPTIONS:

	Options	Available Models
	Chrome-Plated Brass Valve Stainless Steel Handle Steel Cylinder	FE05ABV
	Chrome Cylinder Aluminum Valve	FE05ACC

Dimensions of extinguishers with above options may vary from table below

All units meet the current requirements established by the National Fire Protection Association (NFPA) for NFPA10 "Standard for Portable Fire Extinguishers", and any other applicable NFPA standards. Tested and listed by UL to meet construction and performance standards for this type of extinguisher, and can be used where required by local codes such as OSHA.

Qty.	Model	Type	Nominal Capacity	Shipping Weight	Cylinder Dia.	Overall Height	Overall Width	Shipping Vol. Approx.	UL Rating	Optional Mounting Bracket	USCG Approved
	Cosmic 5X (FE05XA)	ABC Dry Chemical	5 lbs.	9.25 lbs.	4-1/4"	15-1/4"	7-1/4"	.35 cu.ft.	2A-10B:C	MB818A	YES
	Cosmic 5X (FE05XBA)		5 lbs.	9.5 lbs.	4-1/4"	15-1/4"	7-1/4"	.35 cu.ft.	2A-10B:C	MB818A*	YES

*Indicates mounting bracket standard. J hook wall bracket standard with all other extinguisher - mounting bracket available for those models at extra charge.

Note: NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area.

ACTIVAR
CONSTRUCTION PRODUCTS GROUP INC.



800-554-6077
sales@activarcpg.com
www.activarcpg.com

9702 Newton Ave S. Bloomington, MN 55431 | Many Locations Across North America

Distributor:

Project:

Contractor:

Approved By:

Date:

Architect:

Scale: N/A

Pages: 1 of 1

Item #: