

## FIRE EXTINGUISHERS - MERCURY HALOTRON® - Portable Handheld

The Halotron® I clean agent is an excellent replacement for Halon 1211 extinguishers. Because the extinguishing agent leaves no residue, it is ideal for protecting sensitive electronic equipment, laboratories, museums and vehicle maintenance facilities.



### CLASS B FIRES

Flammable  
Liquids  
and Gases



### CLASS C FIRES

Energized  
Electrical  
Equipment

## SPECIFICATIONS:

This model contains the clean extinguishing agent Halotron® 1, which is EPA-approved, government accepted and specified. This agent discharges as a liquid, then quickly evaporates, leaving no residue to clean up afterwards. U.S. FAA-approved for use in airports. NFPA-10 rating. Electrically non-conductive.

**Conforms to Test Standards:** CAN/ULC-S556-ANSI/UL2129 & CAN/ULC-S508-ANSI/UL711

**Operation:** Squeeze the lever, which opens the valve, allowing the chemical to be forced out.

**Temperature Range:** -40° F (-40° C) to 120° F (49° C)

**Construction:** Drawn steel cylinder with steel siphon tubes, power cone discharge stream, upright squeeze grip visual pressure gauge and corrosion-resistant paint finish.


**Valve Material:** Aluminum

## OPTIONS AT ADDITIONAL COST:

Options		Available Models
Brass Valve Steel Cylinder		Mercury 11, Mercury 15-1/2
Aluminum Valve Chrome Cylinder		Mercury 2-1/2, Mercury 5

*Dimensions of extinguishers with above options may vary from table below*

All units meet the current requirements established by the National Fire Protection Association (NFPA) for NFPA10 "Standard for Portable Fire Extinguishers", and any other applicable NFPA standards. Tested and listed by UL to meet construction and performance standards for this type of extinguisher, and can be used where required by local codes such as OSHA.

Qty.	Model	Type	Nominal Capacity	Shipping Weight	Cylinder Dia.	Overall Height	Overall Width	Shipping Vol	UL Rating 	Optional Mounting Bracket	USCG Approved
	<b>Mercury 2-1/2*</b>	Halotron®	2-½ lbs	5-¼ lbs	3-¾"	15-½"	6-¾"	.25 cu.ft.	2B:C	MB817C or MB817A*	N/A
	<b>Mercury 5</b>		5 lbs	9-½ lbs	4-¼"	16-¾"	7-¼"	.3 cu.ft.	5B:C	MB818C or MB818A	YES
	<b>Mercury 11 (FM11C)</b>		11 lbs	21-¼ lbs	7"	17-½"	8-¾"	1.0 cu.ft.	1A-10B:C	MB810C	YES
	<b>Mercury 11 (FM11A)</b>		11 lbs	22-½ lbs	6"	21-¾"	9-¼"	1.0 cu.ft.	1A-10B:C	MB812A	YES
	<b>Mercury 15-1/2 (FM15C)</b>		15-½ lbs	25-¾ lbs	7"	17-½"	8-¾"	1.0 cu.ft.	2A-10B:C	MB810C	YES
	<b>Mercury 15-1/2 (FM15A)</b>		15-½ lbs	27-½ lbs	6"	21-¾"	9-¼"	1.0 cu.ft.	2A-10B:C	MB812A	YES

\*Indicates mounting bracket standard. J hook wall bracket standard with all other extinguisher - mounting bracket available for those models at extra charge.

**Note:** NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area.

**ACTIVAR**  
CONSTRUCTION PRODUCTS GROUP INC.



800-554-6077  
sales@activarcpg.com  
www.activarcpg.com

9702 Newton Ave S. Bloomington, MN 55431 | Many Locations Nationwide

Distributor:

Project:

Contractor:

Approved By:

Date:

Architect:

Scale: N/A

Pages: 1 of 1

Item #: