SUBMITTAL: SM[™] SURFACE-MOUNT ACCESS PANEL

Model SM for Masonry, Tile and Wallboard This all purpose frameless 16 gauge steel access door affords fast and convenient access for inspection or service to vital components of plumbing, heating, air conditioning and/or electrical systems. The SM is primarily used for new installations or remodeling on masonry, tile, wood or other wall surfaces. Screws may be used to fasten the SM model securely in place through mounting holes in each corner.

SPECIFICATIONS SM STEEL

Frame: 16 gauge steel with 1" wall flange.
Door: 16 gauge steel mounted with 90° continuous, concealed hinge.
Finish: White powder coat paint.
Lock: Flush screwdriver-operated steel cam " C".
Sizes: Minimum 8" x 8", maximum wall 36" x 36", maximum ceiling 24" x 24".

SPECIFICATIONS SMS STAINLESS STEEL

Frame: 16 gauge stainless steel with 1" wall flange.
Door: 16 gauge stainless steel mounted with 90° continuous, concealed hinge.
Finish: 304 stainless steel.
Lock: Flush screwdriver-operated steel cam " C".
Sizes: Minimum 8" x 8", maximum wall 36" x 36", maximum ceiling 24" x 24".

STEP 1: SELECT MODEL FROM CHART OR ENTER SIZE:

____ For sizes not shown on chart. _____" W x _____" H (See size ranges above)

STEP 2: SELECT MATERIAL:

- ____ Standard 16 gauge steel SM
- ____ Stainless Steel SMS (additional cost)
- Galvannealed Steel SMG (additional cost)

STEP 3: SELECT OPTIONS AT ADDITIONAL COST:

- Optional Color Code: ____ see page 2
- (L) Cylinder lock installed
- (C2) Torx head cam
- (C3) Spanner head cam
- (C4) Hex head cam
- (C5) Knob cam
- (P1) Paddle handle


JL INDUSTRIES	Distributor:	Quantity:			
	Contractor:	Approved By:			
	Model #:	Architect:			
	Project:	Date:	© 2022 Activar Construction Products Group, Inc		
Headquarters: 9702 Newton Av S, Bloomington, MN 55431 Ph: 800-554-6077 Email: sales@activarcpg.com www.activarcpg.com					
MANUFACTURING: BLOOMINGTON, MN & COMMERCE, CA WAREHOUSES: See website for locations 3/16/2022					

SM 0808

SMS 0808



LATCH AND LOCK OPTIONS Standard Cam Latch Cylinder Lock (L) Torx Head Cam (C2) Spanner Head Cam (C3) Hex Head Cam (C4) Knob Cam (C5) Paddle Handle (P1)



SUBMITTAL: SM[™] SURFACE-MOUNT ACCESS PANEL

Model SM—Surface Mount Access Panel									
QTY	Model Size Width x Height	Outside Frame Dimensions		Wall Opening Dimensions		Shipping Weight	Latch(s)		
		Width	Height	Width	Height				
	8 x 8	10"	10"	8"	8"	3 lbs	1		
	12 x 12	14"	14"	12"	12"	7 lbs	1		
	16 x 16	18"	18"	16"	16"	12 lbs	1		
	24 x 24	26"	26"	24"	24"	27 lbs	4		

Standard Color is White, Optional Colors at Additional Cost - Samples Available								
W (White)	B (Bronze)	R (Red)	BK (Black)	S (Sand)	AB (AMS Beige)	SB (SC Beige)	G (Gray)	SI (Silver)