



ENTRANCE GRATE - Activ-Grate™ EG400 Series - Aluminum Roll-Up Grate

EFSA




EFSA4: Surface-mounted tapered aluminum frame for installation by anchoring to floor. Serrated aluminum 6063-T5 alloy extrusion frame 3/8" (9.5 mm) deep by 1-7/8" (47.6 mm) give traction to the full width of the mat. End filler is provided at both ends to create a snug fit.

EFRA




EFRA4: Angle frame for butting up to tile or carpet. 7/16" (11.1 mm) deep by 1/8" (3.2mm) profile. Extruded aluminum 6063-T5 alloy construction. End filler is provided at both ends to create a snug fit.

EFRT




EFRT4: Frame for transition to door threshold. 1/2" (12.7 mm) deep with 1-1/8" (28.6 mm) face and 1-1/2" extension under tread. Extruded aluminum 6063-T5 alloy construction.

ACTIV-GRATE 400 SERIES INSERTS



EG400 Cross-Section



ACTIV-GRATE™ 400 SERIES:

LDPE HINGES, HEAVY DUTY

JL introduces the new heavy-duty 400 series for heavy foot and cart traffic with a 750 lb wheel load rating. Densely-spaced treads provide more tread surface area than mats, to keep your building cleaner.

FEATURES:

- LDPE hinges keep grating quiet and cushion impact.
- Grating rolls up for easy cleaning beneath.
- Drainage holes between tread rails allows moisture and dirt to fall below mat.

PRODUCT DETAILS:

Material: 6063-T5 and 6063-T6 extruded aluminum alloy tread rails and frames.

Depth: 1/2" (12.7 mm).

Standard Finish: Mill.

Tread Spacing: 1-1/2" (38.1 mm) on center with 8 treads per foot in the direction of travel.

Spacing Between Rails: Heelproof spacing of 5/32"

Rolling Wheel Load Rating: 750 lbs

NOTE:

Verify traffic direction - traffic to run perpendicular to rails.

Maximum single mat size not to exceed 12'-0" (3.66m) in width (dim "x") or 100 sq. ft.

If multiple sections, verify sectioning does not occur in traffic path.

Vinyl filler to be trimmed in field for tight fit.

Mat dimensions allow for clearance between mat section(s) and frame(s) in width (dim "x").

Additional product information including installation instructions may be found at www.activarcpg.com/jl-industries



**Entrance Grate
Activ-Grate™ EG400 Series
Data Sheet**

9702 Newton Ave S. Bloomington, MN 55431 | Many Locations Nationwide

800-554-6077 952-835-2218 sales@activarcpg.com www.activarcpg.com