

SUBMITTAL: FB™ SERIES FIBERGLASS FIRE EXTINGUISHER CABINET

Select the JL FB Series - A Durable, Surface- Mount Fiberglass Cabinet that is Resistant to Salt Air, Chemicals, Moisture, Dust, Insects, Temperature Extremes and Other Harmful Elements.

Construction:

Tub and door are constructed of fiberglass with full rubber-gasketed door, 6" x 9" acrylic view window with rubber gasket seal, and corrosion-resistant aluminum handle. All cabinets come standard with a full-length stainless steel hinge attached by rivets. Door is tightly latched against the gasket by (2) stainless steel snap latches.

UV-resistant, high-visibility red finish with 5" x 9" Fire Extinguisher Lettering.



1373D12





1363D12

1353D12

Qty	Model	Tub Size I.D.			Outside Dimensions			Fire Extinguishers
		W	H (Front)	D	Door W	Door H	Depth	
	1353D12	10 1/4"	23 1/4"	8 1/2"	13 1/4"	26 1/8"	9 3/4"	Cosmic and Galaxy 2-1/2 to 10, Cosmic 20E (FE20C), Sentinel 5, Any Mercury, Saturn 15
	1363D12	12-1/2"	24 1/8"	9"	15 3/4"	27 1/8"	10 1/4"	Any Cosmic, Galaxy, Mercury, Saturn 15, Grenadier , Sentinel 5-10
	1373D12	16"	*33"	12 3/4"	19 5/8"	36 1/8"	14"	Any Cosmic, Galaxy, Mercury, Saturn, Grenadier , Sentinel

* Height measured at center

It is the responsibility of the customer to communicate specifications and product performance requirements that are needed for their application. This document is intended to convey potential product configurations and offerings. It is not to be used to imply or represent a specification or rating, of finished products shipped. Detailed, specific submittals can be created upon request. It is the responsibility of the customer to specify product accordingly to comply with local laws, codes, and ordinances.

 JL INDUSTRIES 9702 Newton Av S. Bloomington, MN 55431	 800-554-6077	Distributor:		Project:
	 sales@activarcpg.com	Contractor:		Approved By:
	 www.activarcpg.com	Date:	Quantity:	Architect:
		Scale: N/A	Pages: 1 of 1	Item #