PULL TO OPEN FIRE ALARM COVER

Cato's quality protective alarm covers, manufactured in the U.S., provides a dent and rust proof alternative to metal. It arrives fully assembled, quick to install, the cover can be opened quickly in case of emergency and remains open during inspection and maintenance.




SPECIFICATIONS:

Body Material: Injection molded of high-density polypropylene, available in red only

Cover Material: Injection molded copolymer polypropylene, available in clear only. Pull handle at the top is designed to ADA specifications.

 $\ensuremath{\textbf{Decals:}}$ UV resistant "PULL TO OPEN" and "FIRE" decals included

Hardware: Mounting hardware and anchors are included Sizes: Refer to table, listing models and dimensions. Available for recessed or surface mounted alarms.



QTY		PREVIOUS MODEL	ALARM MOUNTING	OPENING METHOD	COVER INNER DIMENSION W x H x D	COVER OUTER DIMENSION W x H x D	VIEWABLE WINDOW	WEIGHT
		220R	Recessed Mounted Alarm	Pull to Open	6-¼" x 7-¼" x 1-¾"	7-½" x 8-¼" x 2-¼"	5" Square	1.5 lbs
		2205	Surface Mounted Alarm	Pull to Open	6-½" x 7-½" x 3-¼"	7-½" x 8-¼" x 3-¾"	5" Square	1.7 lbs

ORDER GUIDE - PULL TO OPEN FIRE ALARM COVER - EXAMPLE: ALC22001B

QTY	PREFIX				ALARM MOUNTING			IOUNTING	0	PENING METHOD	OPTIONS		
	ALC	(Alarm Cover)	220	Alarm Covers, polypropylene red		0	R	Recessed	1	Pull to open Unsecured		в	Gasket
						1	S	White tub/body, white trim/frame, red acrylic					

