

FIRE EXTINGUISHERS - ANSUL CLEANGUARD PLUS® Clean Agent - Portable Handheld

Typical applications for the CleanGuard+ are computer centers, data/document and art storage rooms, communications facilities, laboratories and sensitive equipment.



FCGP03 FCGP13 FCGP07 FCGP14-NM



CLASS A FIRES[†]
Common
Combustibles



CLASS B FIRES
Flammable
Liquids
and Gases



CLASS C FIRES
Energized
Electrical
Equipment

SPECIFICATIONS:

Hand portable extinguishers containing FK-5-1-12 clean agent.

FK-5-1-12 agent is a colorless, odorless, electrically non-conductive clean agent which discharges as a liquid and flashes to a gas. FK-5-1-12 has been accepted by the EPA. For commercial, industrial, and military use under the EPA's SNAP program.


Conforms to Test Standards: ANSI/UL2129 & 711 and CAN/ULC S508 & S566

Operation: Squeeze the lever, which opens the valve, allowing the chemical to be forced out. Upright squeeze grip operation.

Temperature Range: -40° F (-40° C) to 120° F (49° C)

Construction: Seamless steel cylinder with powder coat finish. Valve bodies are black anodized.

All units meet the current requirements established by the National Fire Protection Association (NFPA) for NFPA10 “Standard for Portable Fire Extinguishers”, and any other applicable NFPA standards. Tested and listed by UL to meet construction and performance standards for this type of extinguisher, and can be used where required by local codes such as OSHA.

Qty.	Model	Type	Nominal Capacity	Shipping Weight	Cylinder Dia.	Overall Height	Overall Width	Shipping Vol. Approx.	UL Rating 	Optional Mounting Bracket	Fits in Cabinet Series
	FCGP03*	CleanGuard Plus	3-½ lbs.	6 lbs.	3-¾"	14-¼"	5-¾"	.19 cu.ft	2-B:C	MB24610	1800, 1000, 2000, 3000, 4000, 5600, 5700
	FCGP07		7-½ lbs.	12 lbs.	4-7/16"	16-¾"	8-½"	.42 cu.ft	5-B:C	MB429146	
	FCGP13		13 lbs.	20 lbs.	5-¼"	20-½"	8-¼"	.87 cu.ft.	1-A:10-B:C	MB435793	
	FCGP14-NM**	CleanGuard Plus Non-Magnetic**	14 lbs.	19 lbs.	7-⅛"	14-¾"	9-¼"	.93 cu.ft.	1-A:10-B:C	J-HOOK only	2000, 3000, 4000, 5700, 12001, 12051
	FCGP25	CleanGuard Plus	27-¾ lbs.	40lbs.	7-1/10"	23-½"	7-½"	.78 cu.ft.	2-A:10-BC	MB30937	2000, 3000, 4000, 5700

*Mounting bracket included.

**Model FCGP14-NM is constructed of non-conductive stainless steel cylinder, valve, hose & nozzle: Tested to be MR Conditional to 7.0 tesla. Can be mounted within the MRI room.

Note: NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area. Cleanguard® is a trademark of Johnson Controls



JL INDUSTRIES

9702 Newton Ave S. Bloomington, MN 55431 | Many Locations Nationwide



800-554-6077



sales@activarcpg.com



www.activarcpg.com

Distributor:

Contractor:

Date:

Scale: N/A

Project:

Approved By:

Architect:

Item #:

Pages: 1 of 1