

FIRE EXTINGUISHERS - GRENADE PRESSURIZED WATER - C - PORTABLE HANDHELD

The Water extinguisher uses ordinary water as its extinguishing agent, and can be pressurized with regular air, making recharging the extinguisher simple and economical.



CLASS A FIRES
Common
Combustibles

SPECIFICATIONS:

Pressurized Water Extinguishers for Class "A" Fires. The "water press" extinguisher contains water and compressed air. Units shipped empty.

Conforms to Test Standards: CAN/ULC-S507-ANSI/UL626 and CAN/ULC S508-ANSI/UL711

Operation: Squeeze the lever, which opens the valve, allowing the water to be forced out. Upright squeeze grip operation.

Temperature Range: 40° F (4° C) to 120° F (49° C)

Construction: Butt-welded 304-L stainless steel cylinder (eliminates all internal and external crevices). Rugged stainless steel discharge lever and fixed carry handle with visual pressure gauge, pull pin. All-metal valve body with replaceable molded valve stem seal. UL labeled chemical engine hose.

All units meet the current requirements established by the National Fire Protection Association (NFPA) for NFPA10 "Standard for Portable Fire Extinguishers", and any other applicable NFPA standards. Tested and listed by UL to meet construction and performance standards for this type of extinguisher, and can be used where required by local codes such as OSHA.


Qty.	Model	Description	Type	Nominal Capacity	Shipping Weight	Cylinder Dia.	Overall Height	Overall Width	Shipping Vol	UL Rating	Optional Mounting Bracket	USCG Approved
	FP02C	Grenadier-P	Water	2-½ gal.	8.3 lbs.	7"	24-½"	9"	1.1 cu.ft.	2A	MB810C	YES

J Hook wall bracket standard - Mounting bracket available at extra charge.

Note: NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area.

«The Grenadier Extinguisher is shipped empty.

It is the responsibility of the customer to communicate specifications and product performance requirements that are needed for their application. This document is intended to convey potential product configurations and offerings. It is not to be used to imply or represent a specification or rating, of finished products shipped. Detailed, specific submittals can be created upon request. It is the responsibility of the customer to specify product accordingly to comply with local laws, codes, and ordinances.

 <p>JL INDUSTRIES 9702 Newton Ave S. Bloomington, MN 55431 Many Locations Across North America</p>	<p>800-554-6077</p> <p>sales@activarcpg.com</p> <p>www.activarcpg.com</p>	<p>Distributor:</p>	<p>Project:</p>
		<p>Contractor:</p>	<p>Approved By:</p>
		<p>Date:</p>	<p>Architect:</p>
	<p>Scale: N/A</p>	<p>Pages: 1 of 1</p>	<p>Item #:</p>