

FIRE EXTINGUISHERS - MERCURY HALOTRON® - Portable Handheld

The Halotron® I clean agent is an excellent replacement for Halon 1211 extinguishers. Because the extinguishing agent leaves no residue, it is ideal for protecting sensitive electronic equipment, laboratories, museums and vehicle maintenance facilities.

SPECIFICATIONS:

This model contains the clean extinguishing agent Halotron® 1, which is EPA-approved, government accepted and specified. This agent discharges as a liquid, then quickly evaporates, leaving no residue to clean up afterwards. U.S. FAA-approved for use in airports. NFPA-10 rating. Electrically non-conductive.

Conforms to Test Standards: CAN/ULC-S556-ANSI/UL2129 & CAN/ULC-S508-ANSI/UL711

Operation: Squeeze the lever, which opens the valve, allowing the chemical to be forced out.

Temperature Range: -40° F (-40° C) to 120° F (49° C)

Construction: Drawn steel cylinder with steel siphon tubes, power cone discharge stream, upright squeeze grip visual pressure gauge and corrosion-resistant paint finish.

Valve Material: Aluminum



CLASS B FIRES


Flammable
Liquids
and Gases



CLASS C FIRES

Energized
Electrical
Equipment

All units meet the current requirements established by the National Fire Protection Association (NFPA) for NFPA10 "Standard for Portable Fire Extinguishers", and any other applicable NFPA standards. Tested and listed by UL to meet construction and performance standards for this type of extinguisher, and can be used where required by local codes such as OSHA.

Qty.	Model	Type	Nominal Capacity	Shipping Weight	Cylinder Dia.	Overall Height	Overall Width	Shipping Vol	UL Rating 	Optional Mounting Bracket	USCG Approved
	Mercury 2-1/2* (FM02C)	Halotron®	2-½ lbs	5-¼ lbs	3-¾"	13-¾"	6-¾"	.25 cu.ft.	2B:C	MB817C*	N/A
	Mercury 5* (FM05C)		5 lbs	9-½ lbs	4-¼"	16-¾"	7-¼"	.3 cu.ft.	5B:C	MB818C*	YES
	Mercury 11 (FM11C)		11 lbs	21-¼ lbs	7"	17-½"	8-¾"	1.0 cu.ft.	1A-10B:C	MB810C	YES
	Mercury 15 (FM15C)		15-½ lbs	25-¾ lbs	7"	17-½"	8-¾"	1.0 cu.ft.	2A-10B:C	MB810C	YES

*Indicates mounting bracket standard. J hook wall bracket standard with all other extinguisher - mounting bracket available for those models at extra charge.

Note: NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area.



JL INDUSTRIES

800-554-6077

sales@activarcpg.com

www.activarcpg.com

9702 Newton Ave S. Bloomington, MN 55431 | Many Locations Across North America

Distributor:

Contractor:

Date:

Scale: N/A

Project:

Approved By:

Architect:

Item #:

Pages: 1 of 1