FIRE EXTINGUISHERS - MERCURY HALOTRON® - C -PORTABLE HANDHELD

The Halotron® I clean agent is and excellent replacement for Halon 1211 extinguishers. Because the extinguishing agent leaves no residue, it is ideal for protecting sensitive electronic equipment, laboratories, museums and vehicle maintenance facilities.

CLASS A FIRES

Common Combustibles

CLASS B FIRES

Flammable Liquids and Gases

CLASS C FIRES

Energized Electrical Equipment

SPECIFICATIONS:

This model contains the clean extinguishing agent Halotron® 1, which is EPA-approved, government accepted and specified. This agent discharges as a liquid, then quickly evaporates, leaving no residue to clean up afterwards. U.S. FAA-approved for use in airports. NFPA-10 rating. Electrically non-conductive.

Conforms to Test Standards: CAN/ULC-S556-ANSI/UL2129 & CAN/ULC-S508-ANSI/UL711

Operation: Squeeze the lever, which opens the valve, allowing the chemical to be forced out.

Temperature Range: -40° F (-40° C) to 120° F (49° C)

Construction: Drawn steel cylinder with steel siphon tubes, power cone discharge stream, upright squeeze grip visual pressure gauge and corrosion-resistant paint finish.

Valve Material: Aluminum

All units meet the current requirements established by the National Fire Protection Association (NFPA) for NFPA10 "Standard for Portable Fire Extinguishers", and any other applicable NFPA standards. Tested and listed by UL to meet construction and performance standards for this type of extinguisher, and can by used where required by local codes such as OSHA.

Qty.	Model	Description	Type	Valve	Nominal Capacity	Shipping Weight	Cylinder Dia.	Overall Height	Overall Width	Shipping Vol	UL Rating	Optional Mounting Bracket	USCG Approved
	FM02C	**Mercury 2-1/2***	Halotron®	Aluminum	2-½ lbs	5-½ lbs	3-⅜"	13-⅜"	6-⅝"	.25 cu.ft.	2B:C	MB817C*	N/A
	FM05C	**Mercury 5***			5 lbs	9-½ lbs	4-¼"	16-⅜"	7-¼"	.3 cu.ft.	5B:C	MB818C*	YES
	FM11C	**Mercury 11**			11 lbs	21-¼ lbs	7"	17-½"	8-⅝"	1.0 cu.ft.	1A-10B:C	MB810C	
	FM15C	**Mercury 15**			15-½ lbs	25-¾ lbs	7"	17-½"	8-⅝"	1.0 cu.ft.	2A-10B:C	MB810C	
	FM11CBV	**Mercury 11**		Brass	11 lbs	21-¼"	7"	17-½"	8-⅝"	1.0 cu.ft.	1A-10B:C	MB810C	
	FM15CBV	**Mercury 15**			15-½ lbs	25-¾ lbs	7"	17-½"	8-⅝"	1.0 cu.ft.	2A-10B:C	MB810C	

*Indicates mounting bracket standard. J hook wall bracket standard with all other extinguisher - mounting bracket available for those models at extra charge.
Note: NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area.

It is the responsibility of the customer to communicate specifications and product performance requirements that are needed for their application. This document is intended to convey potential product configurations and offerings. It is not to be used to imply or represent a specification or rating, of finished products shipped. Detailed, specific submittals can be created upon request. It is the responsibility of the customer to specify product accordingly to comply with local laws, codes, and ordinances.

JL INDUSTRIES
800-554-6077
sales@activarcpg.com
www.activarcpg.com
9702 Newton Ave S. Bloomington, MN 55431 | Many Locations Across North America

Distributor:		Project:
Contractor:		Approved By:
Date:		Architect:
Scale: N/A	Pages: 1 of 1	Item #:

© 2026 Activar Construction Products Group, Inc.
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ACTIVAR CONSTRUCTION PRODUCTS GROUP, INC.
ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ACTIVAR CONSTRUCTION PRODUCTS GROUP, INC. IS PROHIBITED.