## FIRE EXTINGUISHERS - ORBIT PURPLE K DRY CHEMICAL - Portable Handheld

Purple K extinguisher is suitable flammable liquid hazards in public areas such as offices, classrooms, churches, garages, service bays, boats, vehicles, fuel storage and transfer areas. It is not recommended for use on sensitive electronic equipment







**CLASS B FIRES** 

**CLASS C FIRES** 

Flammable Liquids and Gases

Energized Electrical Equipment





Button Hook for FPK10VB

## SPECIFICATIONS:

The Orbit Fire Extinguisher is as much as 40 percent slimmer than traditional 10-lb. models, allowing for more efficient and elegant building design. It is the only 10-lb. fire extinguisher that is always compliant with ADA protruding object regulations and local building codes.

## **Purple K**

Contain specially fluidized and siliconized potassium bicarbonate dry chemical which is particularly effective on Class B flammable liquids and pressurized gases. It is electrically non-conductive. Purple K is the preferred fire fighting agent of oil, gas, chemical and utilities industries

Conforms to Test Standards: CAN/ULC-S504 — ANSI/UL299 & CAN/ULC S508 — ANSI/UL711

**Operation:** Squeeze the lever, which opens the valve, allowing the chemical to be forced out. Upright squeeze grip operation. Approved to -40°F (-40°C) - 120° F (49°C)

**Construction:** Non-Magnetic corrosion-resistant tempered aluminum vessel with aluminum valve and siphon tube. Also features visual pressure gauge, stainless steel pull pin, handles, bracket and button hook. Durable powder coat finish. Tested to 3 Tesla.

Valve Material: Aluminum

All units meet the current requirements established by the National Fire Protection Association (NFPA) for NFPA10 "Standard for Portable Fire Extinguishers", and any other applicable NFPA standards. Tested and listed by UL to meet construction and performance standards for this type of extinguisher, and can by used where required by local codes such as OSHA.

Qty.	Model	Туре	Nominal Capacity	Shipping Weight	Cylinder Dia.	Overall Height	Overall Width	Shipping Vol. Approx.	UL Rating 🕕	Mounting	USCG Approved
	FPK10VB	Purple K	10 lbs.	22 lbs.	3.5"	23"	9"	1.35 cu.ft.	80B:C	Surface	

Note: NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area.

It is the responsibility of the customer to communicate specifications and product performance requirements that are needed for their application. This document is intended to convey potential product configurations and offerings. It is not to be used to imply or represent a specification or rating, of finished products shipped. Detailed, specific submittals can be created upon request. It is the responsibility of the customer to specify product accordingly to comply with local laws, codes, and ordinances.





Distributor:		Project:			
Contractor:		Approved By:			
Date:		Architect:			
Scale: N/A	Pages: 1 of 1	Item #:			