

## FIRE EXTINGUISHERS - Dry Chemical - Portable Wheeled

Standard BC dry chemical is a multipurpose that is suitable for use on flammable liquid hazards in areas such as light manufacturing facilities, vehicle/aircraft/marine service centers and retail stores



**CLASS B FIRES**  
Flammable Liquids  
and Gases



**CLASS C FIRES**  
Energized Electrical  
Equipment

### SPECIFICATIONS:

Portable, large-capacity extinguisher units contain a siliconized sodium bicarbonate base, the traditional dry chemical. Cleanup after use is generally easy, because the chemical does not normally bake to a hot metal surface. Non-toxic.


**Conforms to Test Standards:** CAN/ULC-S504 — ANSI/UL299 & CAN/ULC S508 — ANSI/UL711

Designed for one man operation these units are easily transportable through doorways and over rough terrain. Operating Temperature Range: -65°F (-54°C) to 120°F (49°C).

**Construction:** Cylinders are manufactured to DOT specification 4BW240. Highly visible pressure-indicating gauge. Cylinders and carriages are shot blasted, primed and coated with the finest polyurethane powder paint finish that exceeds Underwriter's Laboratories 240 hour salt spray requirements. Hoses are included. All component parts are replaceable. Tow loops are available upon request. Tow loops allow for low speed (15 MPH) towing over gravel or paved surfaces. All units are equipped with all weather semi-pneumatic 12.3 inch diameter, 3.5 inch wide tires.

**Valve Material:** Chrome plated brass

All units meet the current requirements established by the National Fire Protection Association (NFPA) for NFPA10 "Standard for Portable Fire Extinguishers", and any other applicable NFPA standards. Tested and listed by UL to meet construction and performance standards for this type of extinguisher, and can be used where required by local codes such as OSHA.

Qty.	Model	Type	Nominal Capacity	Shipping Weight	Overall Height <i>In Inches</i>	Overall Width <i>In Inches</i>	Overall Depth <i>In Inches</i>	Hose Length & Diameter	UL Rating 	Wheel Type	Wheel Dia. <i>In Inches</i>	USCG Approved
	8FW31220	BC Dry Chemical	150 lbs.	412 lbs.	50	24	42	50 ft. x .75 in.	240-B:C	Rubber	16.4 x 4	--
	8FW31240		150 lbs.	447 lbs.	55	32	46	50 ft. x .75 in.	240-B:C	Steel	36 x 2.5	--
	8FW31250		150 lbs.	459 lbs.	55	32	46	50 ft. x .75 in.	240-B:C	Steel w/Rubber Tread	36 x 2.5	--
	8FW31210		150 lbs.	350 lbs.	50	24	42	50 ft. x .75 in.	240-B:C	Rubber	16.4 x 4	--
	8FW32220		350 lbs.	830 lbs.	58	36	48	50 ft. x 1 in.	320-B:C	Steel	36 x 6	--
	8FW32240		350 lbs.	856 lbs.	58	36	48	50 ft. x 1 in.	320-B:C	Steel w/Rubber Tread	36 x 6	--
	8FW32210		350 lbs.	707 lbs.	58	36	48	50 ft. x 1 in.	320-B:C	Steel	36 x 6	--
	8FW32230		350 lbs.	733 lbs.	58	36	48	50 ft. x 1 in.	320-B:C	Steel w/Rubber Tread	36 x 6	--

**Note:** NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area.



800-554-6077  
sales@activarcpg.com  
www.activarcpg.com

9702 Newton Ave S. Bloomington, MN 55431 | Many Locations Nationwide

Distributor:	Project:
Contractor:	Approved By:
Date:	Architect:
Scale: N/A	Pages: 1 of 1
	Item #: