LOUVER—BOLTED TO DOOR

MODELS: 600A, 600C, 700A, 800A, 800C, 900A, 900C, 1200A, 1300A, 1300C, 1400A, 1400C


INSTALLATION AND MAINTENANCE GUIDE


GENERAL:


- Read and follow the installation requirements of the door manufacturer.
- Cut the hole in the door to correspond to the order size of the louver. Assure that the opening is plumb and square.
- Insert corridor half of the louver into the cutout, make sure to center in opening.
- <u>Wood doors</u>: screw into door through holes. Tighten the screws alternately in a criss-cross pattern to avoid putting more pressure on one side than the other. Do not tighten to the point of deflecting the frame.
- <u>Metal doors</u>: use this as a template to mark to drill holes for the screws.
- Remove louver and drill 1/8" pilot holes. Reinsert, and install using screws provided. Tighten the screws alternately in a crisscross pattern to avoid putting more pressure on one side than the other. Do not tighten to the point of deflecting the frame.
- **Dual Side Mounting:** Align room side of the louver with installed side (when closed adjusting tab on model 1200 angles down). Mount as per #4 or #5 above.

Check movement of louver adjustment for model 1200.

Single Side Mounting: Apply stop to room side of louver.







Room Side

Corridor Side

Material	Finish Description		Cleaning & Maintenance	
Steel	Powder Coat Paint		Lice a coft cloth and mild coan and water	
Aluminum	Mill		Use a soft cloth and mild soap and water.	
Stainless Steel	304 Stainless Steel with #4 finish (US32D)		Use a soft cloth and mild soap and water solution. After cleaning, thoroughly rinse with clear water to remove all traces of the solution and wipe dry to prevent water marks from forming. Stains which resist that treatment can usually be removed by polishing in the di- rection of the grain with a soft cloth and a non-abrasive stainless steel polish such as Mr. Metal by Northern Labs. Test in an unobtru- sive area. Do not used steel wool or a wire brush which may embed particles into the product and rust.	
		6077 ctivarcpg.com ivarcpg.com	LOUVER BOLTED TO DOOR	
9702 Newton Av S. Bloomington, MN 55431 Many Location		ons Nationwide	Page 1 of 1	
				of Activar Construction Products Group, Inc. Any reproduc- Construction Products Group, Inc. is prohibited. MAY 23, 2022

Dual Side (A) Mounting Option