SUBMITTAL: CROWNLINE™ VALVE & HOSE CABINETS - STAINLESS STEEL

Crownline Cabinets Provide A Wide Selection of Door Styles, Glazing and Sizes. These Durable Cabinets are Designed to Industry Standards for Fire Department Valves, Fire Hose Rack Units and Extinguishers.

Door & Trim: #4 Brushed finish stainless steel. 1-3/4" Trim on face and door. These flush cabinet doors are mounted in a 5/8" door stop, are attached by a continuous hinge, and are equipped with zinc-plated handle and roller catch for all nonlocking doors. Theft-deterrent SAF-T-LOK™ also available.

Trim Style and Depth: 1-3/4" face trim on frame and 1-1/4" trim on door. Recessed - 3/8" flat trim. Semi-recessed - 1-1/4" Square Edge or 2-1/2" Rolled Edge. Surface mounted - Rolled edge. See separate submittal for trimless models.

Tub: CRS, white powder-coat finish standard. Surface-mounted tubs are of the same material as the door and trim.

Knockouts: 6000, 7000 & 8000 Series-K.O.'s provided on both sides of the tub; top and bottom. 8400, 8500, 8600 & 8700 Series-one K.O. provided on each side of the tub; centered. K.O.'s are not provided with a stainless tub option or on surface-mounted cabinets. "J" & "K" dimension is to be measured from the back of the tub.

See Page 2 for Drawing of K.O. locations.

Fire-Rated Option Available: Yes - See separate submittal.

ADA Cabinet Mounting Height: Standard Pull on G, E, W, A,L22 and B Door Styles with Saf-T-Lok are 3 5/8" Higher than Door Center, so Allow for that When Mounting Cabinet. Standard Pull with No Lock or ADA Recessed Pull are Centered on Door.

STEP 1: SELECT MODEL NUMBER, TRIM & QUANTITY (Refer to Chart on Page 2)

STEP 2: SELECT DOOR STYLE F Full Glazing G Full Glazing with SAF-T-LOK	<u> </u>		G - Full gla handle and	ss with pull ss with pull I Saf-T-Lok thown)	D - Horizontal duo panel with pull E - Horizontal duo panel with pull and Sai -T-Lok. (Not Shown)	V - Vertical duo panel with pull W - Vertical duo f panel with pull and Saf-T-Lok. (Not Shown)
D Horizontal Duo Panel E Horizontal Duo Panel with SAF-T-LOK A Center Duo Panel with SAF-T-LOK S21 Solid Door		 V Vertical Duo with SAF-T-LOK Acrylic View Window with SAF-T-LOK 24 Solid with Cylinder Lock & No Handle 			•	0
STEP 3: SELECT DOOR GLAZING 10 Clear Acrylic 13 Clear Wire Glass with Safety Film 15 Bronze Acrylic		Check one box below) 6 Gray Acrylic 7 Clear Tempered Glass 8 Laminated Safety Glass	S21 - Solid L22 - Solid and Saf- L24 - Solid v der key loc	with pull T-Lok with cylin-	B10 - Acrylic view window with pull, and Saf-T-Lok	A - Horizontal duo panel with pull and Saf-T-Lok
STEP 4: OPTIONAL FEATURES AT ADDI		COST:	(L22,24 no			
#6 Matte Finish Stainless Steel Door & Trim #7 Polished Stainless Steel Door & Trim #8 Mirror Finish Stainless Steel Door & Trim #4 Finish Stainless Tub Optional Tub Color: BlackRed SA Strobe Alarm (surface mount models) CA Commander Alarm BA Brigadier Alarm Futura "Fire" Handle Mill Red White Shelf for 8000 Series - 12" from top of Cabine	PUCH FDVO 1403 I LDCH LDCV LDCV LDCV LDCV	Recessed Pull Handle Polished Chrome Pull Decal Fire Department Valve Octagonal 6 x 6" Decal Fire Hose Black/Red Horiz. Letters 4 x 9 RFDV-R Diecut Fire Dept. Valve Horiz. 10-1/4 x 4-3/8 RFDV Diecut Fire Dept Valve Vert. 3/4" x 21½" RFDV-R Diecut Fire Dept Valve Vert. Rever. 3/4" x 21 RFDV Diecut Fire Department Valve Ascend. 1" x 17 RFSCV-R Diecut Fire Sprinkler Cont. Valve Vert 3/4	" •" x 18" Fir	Red Ve White V Black H Red Ho White H Engrave Door (e Check t e Hose R	ed Door or Silkso xcept #7 or #8 fi pox and attach s acks - See sepa	LDCVRFE rs LDCVWFE ters LDCHBFE ers LDCHRFE etters LDCHRFE etters LDCHWFE creen on Glass or nish) Etched Gls, eparate submittal arate submittal
It is the responsibility of the customer to communicate spe tial product configurations and offerings. It is not to be us request. It is the responsibility of the customer to specify	ed to imply	and product performance requirements that are needed for th or represent a specification or rating, of finished products ship ordingly to comply with local laws, codes, and ordinances.	neir applica oped. Deta	tion. This iled, specif	document is intend fic submittals can b	led to convey poten- e created upon
		Distributor:	Quan	tity:		

	Distributor:	Quantity:						
JL INDUSTRIES	Contractor:	Approved By:						
	Model #:	Architect:						
©2023 Activar Construction Products Group, Inc.	Project:	Date:						
Headquarters: 9702 Newton Ave S, bloomington, MN 55431 Ph: 800-554-6077 Email: sales@activarcpg.com www.activarcpg.com Manufacturing: Bloomington, MN & Commerce, CA Warehouses: See website for locations 12/22/2023								





PG 1 OF 2

SUBMITTAL: CROWNLINE VALVE & HOSE CABINETS - STAINLESS STEEL PAGE 2 OF 2

						1								
									///////////////////////////////////////					
*		Cabinets	4"	×.				13			Ľ			
1	21 •	or less	•				d	귝띧						
		Projectio	n						्न्दी		T JU	U.		
1		in Blue			3" (.9cm)	1	-1/4" (/2" (6.4			<u>d</u>	
1				FL/	AT TRIM		SQUAR	ETRIM	RO	LLED ED	GE	su	JRFACE MOUNT	
TOULO			N 147 11	D '			DEA				0.01/			
I RIM & L	DOOR MATERIAL &		D. W x H x	Din	FRAME	0.D.		ESSED \					RECOMMENDED HOSE RACK, FIRE DEPARTMENT VALVES &	
QTY #	SERIES TRIM STYLE		Inches	С	F	-		OPENIN(Height			CATIC G		EXTINGUISHERS	
	IRINISITLE	Α	B		E Hose Ra	F ok ond				J	_	K	EXTINGUISHERS	
6035	FLAT TRIM 3/8"	24	30	6	27 3/8	33 3/8	25	31	5 7/8	2 1/2	11 Val	ve 2 1/2	HOSE RACK:	
6035	1-1/4" SQUARE EDGE		30	6	27 3/8	33 3/8	25	31	4 7/8	2 1/2	4	2 1/2	1- 1/2" x 1-1/2" Hose Rack Unit -	
6037	2-1/2" ROLLED EDGE		30	6	27 3/8	33 3/8	25	31	3 5/8			Ordering	50 or 75' Hose (HRA050B, HRA050CH,	
6039	SURFACE MOUNTED		33 3/16	6 1/2	27 3/8	33 3/8	-	-	-		t Avail	U	HRA075B, HRA075CH) & Cosmic 2.5 or	
		27 3/10									1		Galaxy 2.5-5 lb Extinguisher	
6235 6236	FLAT TRIM 3/8" 1-1/4" SQUARE EDGE		34 3/4 34 3/4	6 6	27 3/8 27 3/8	38 1/8 38 1/8	25 25	35 3/4 35 3/4	5 7/8 4 7/8	2 1/2 2 1/2	4	2 1/2 2 1/2	HOSE RACK:	
6236	2-1/2" ROLLED EDGE		34 3/4	6	27 3/8	38 1/8	25 25	35 3/4	4 7/8 3 5/8			2 1/2 Ordering	1- 1/2" x 1-1/2" Hose Rack Unit -100' Hose (HRA100B OR HRA100CH) & Cosmic 2.5	
6239	SURFACE MOUNTED		37 15/16	6 1/2	27 3/8	38 1/8	- 25	- -	3 5/0		t Avail	-	or Galaxy 2.5-5 lb Extinguisher	
6135	FLAT TRIM 3/8"	27 3/10	37 13/10	8	27 3/8	33 3/8	- 25	31	- 7 7/8	4	4	2 1/2		
6136	1-1/4" SQUARE EDGE		30	8	27 3/8	33 3/8	25	31	6 7/8	4	4	2 1/2	HOSE RACK: 2-1/2" x 1-1/2" Hose Rack Unit -	
6137	2-1/2" ROLLED EDGE		30	8	27 3/8	33 3/8	25	31	5 5/8	4	4	2 1/2	50 or 75' Hose	
6139	SURFACE MOUNTED		33 3/16	8 1/2	27 3/8	33 3/8	-	-			t Avail		(H4A050B-2.5 OR HRA075B-2.5)	
6435	FLAT TRIM 3/8"	27 3/10	34 3/4	8	27 3/8	38 1/8	25	35 3/4	7 7/8	4	4	2 1/2	· · · · · · · · · · · · · · · · · · ·	
6436	1-1/4" SQUARE EDGE		34 3/4	8	27 3/8	38 1/8	25	35 3/4	6 7/8	4	4	2 1/2	HOSE RACK:	
6437	2-1/2" ROLLED EDGE		34 3/4	8	27 3/8	38 1/8	25	35 3/4	5 5/8	4	4	2 1/2	2-1/2" x 1-1/2" Hose Rack Unit -	
6439	SURFACE MOUNTED		37 15/16	8 1/2	27 3/8	38 1/8	-	-	-		t Avail	-	100' Hose (HRA100B-2.5)	
6635	FLAT TRIM 3/8"	24	38 3/4	8	27 3/8	42 1/8	25	39 3/4	7 7/8	4	4	2 1/2		
6636	1-1/4" SQUARE EDGE		38 3/4	8	27 3/8	42 1/8	25	39 3/4	6 7/8	4	4	2 1/2	HOSE RACK:	
6637	2-1/2" ROLLED EDGE		38 3/4	8	27 3/8	42 1/8	25	39 3/4	5 5/8	4	4	2 1/2	2-1/2" x 1-1/2" Hose Rack Unit -	
6639	SURFACE MOUNTED		41 15/16	8 1/2	27 3/8	42 1/8	_	-	-		t Avail		125' Hose (HRA125B-2.5)	
6335	FLAT TRIM 3/8"	30	30	8	33 3/8	33 3/8	31	31	7 7/8	4	4	2 1/2	HOSE RACK & FD VALVE	
6336	1-1/4" SQUARE EDGE		30	8	33 3/8	33 3/8	31	31	6 7/8	4	4	2 1/2	OR EXTINGUISHER:	
6337	2-1/2" ROLLED EDGE		30	8	33 3/8	33 3/8	31	31	5 5/8	4	4	2 1/2	1-1/2" OR 2-1/2" Valve; 50' or 75' Hose	
6339	SURFACE MOUNTED		33 3/16	8 1/2	33 3/8	33 3/8	_	_	_	No	t Avail	able	Rack Unit Plus FD Valve or Cosmic or Galaxy Extinguisher	
6535	FLAT TRIM 3/8"	32 3/4	34 3/4	8	36 1/8	38 1/8	33 3/4	35 3/4	7 7/8	4	4	2 1/2	HOSE RACK & FD VALVE	
6536	1-1/4" SQUARE EDGE		34 3/4	8	36 1/8	38 1/8	33 3/4	35 3/4	6 7/8	4	4	2 1/2	OR EXTINGUISHER:	
6537	2-1/2" ROLLED EDGE		34 3/4	8	36 1/8	38 1/8	33 3/4	35 3/4	5 5/8	4	4	2 1/2	1-1/2" OR 2-1/2" Valve; 100' Hose Rack	
	SURFACE MOUNTED		37 15/16	8 1/2	36 1/8	38 1/8	_	00 0/4	0 0/0	-	t Avail		Unit Plus FD Valve or Cosmic or Galaxy	
								-	-		r		Extinguisher HOSE RACK & FD VALVE	
	FLAT TRIM 3/8"	32 3/4	38 3/4	8	36 1/8	42 1/8	33 3/4		7 7/8	4	4	2 1/2	OR EXTINGUISHER:	
7236 7237	1-1/4" SQUARE EDGE 2-1/2" ROLLED EDGE		38 3/4 38 3/4	8 8	36 1/8 36 1/8	42 1/8 42 1/8	33 3/4 33 3/4	39 3/4 39 3/4	6 7/8 5 5/8	4	4	2 1/2 2 1/2	1-1/2" OR 2-1/2" Valve; 125' Hose Rack	
-				-			33 3/4	39 3/4	0 J D/O		1		Unit Plus FD Valve or Cosmic or Galaxy	
7239	SURFACE MOUNTED	35 15/16	41 15/16	8 1/2	36 1/8	42 1/8	-	-	-	No	t Avail	able	Extinguisher	
		10	40	6			1	artment		4	<u>^</u>	0.4/2		
	FLAT TRIM 3/8"	18	18	8	21 3/8	21 3/8	19	19	7 7/8	4	9	2 1/2		
8536	1-1/4" SQUARE EDGE 2-1/2" ROLLED EDGE		18	8	21 3/8	21 3/8 21 3/8	19	19 19	6 7/8	4	9 9	2 1/2 2 1/2	FIRE DEPARTMENT VALVE:	
	2-1/2" ROLLED EDGE SURFACE MOUNTED		18 21 3/16	8 8 1/2	21 3/8 21 3/8	21 3/8	19 -	- 19	5 5/8	4 No	9 t Avail		1-1/2" or 2-1/2"	
	FLAT TRIM 3/8"	18	18	10	21 3/8	21 3/8	- 19	- 19	- 9 7/8	5	9	able 5	Fire Department Valve with	
8436	1-1/4" SQUARE EDGE		18	10	21 3/8	21 3/8	19	19	87/8	5	9	5	Cap and Chain	
	2-1/2" ROLLED EDGE		18	10	21 3/8	21 3/8	19	19	7 5/8	5	9	5	One K.O. provided on each side of tub	
8439	SURFACE MOUNTED		21 3/16	10 1/2	21 3/8	21 3/8	-	-	-		t Avail	v		
8735	FLAT TRIM 3/8"	26	26	8	29 3/8	29 3/8	27	27	7 7/8	4	13	2 1/2		
8736	1-1/4" SQUARE EDGE		26	8	29 3/8	29 3/8	27	27	6 7/8	4	13	2 1/2	DUAL SIDE BY SIDE	
8737	2-1/2" ROLLED EDGE		26	8	29 3/8	29 3/8	27	27	5 5/8	4	13	2 1/2	FD VALVES & EXTINGUISHER	
8739	SURFACE MOUNTED		29 3/16	8 1/2	29 3/8	29 3/8	-	-	-	No	t Avail	able	OR 2 FD VALVES:	
8635	FLAT TRIM 3/8"	26	26	10	29 3/8	29 3/8	27	27	9 7/8	5	13	5	1-1/2" or 2-1/2" with Cap and Chain Plus	
8636	1-1/4" SQUARE EDGE		26	10	29 3/8	29 3/8	27	27	8 7/8	5	13	5	Extinguisher - Cosmic & Galaxy 2-1/2 to 10 One K.O. provided on each side of tub	
8637	2-1/2" ROLLED EDGE		26	10	29 3/8	29 3/8	27	27	7 5/8	5	13	5	One N.O. provided on each side of lub	
8639	SURFACE MOUNTED		29 3/16	10 1/2	29 3/8	29 3/8	-	-	-		t Avail			
8035	FLAT TRIM 3/8"	16	40	9	19 3/8	43 3/8	17	41	8 7/8	4 1/4	4	4 1/4	DUAL EXTINGUISHER & FD VALVE	
8036	1-1/4" SQUARE EDGE		40	9	19 3/8	43 3/8	17	41	7 7/8	4 1/4	4	4 1/4	CABINET:	
	2-1/2" ROLLED EDGE		40	9	19 3/8	43 3/8	17	41	6 5/8	4 1/4	4	4 1/4	Cosmic or Galaxy Extinguisher	
8039	SURFACE MOUNTED	19 3/16	43 3/16	9 1/2	19 3/8	43 3/8	-	-	-	No	t Avail	able		