

CUSTOM PAK OPTION: PACKAGED KIT, GLAZING, TAPE APPLIED

STEP 1: Select Glazing

Group A: PPF Pyran Platinum F up to 90 minutes —Fire Protective
3/16" to 1/4" WS WireShield up to 90 minutes —Fire Protective
Thickness TEMP Tempered
 See Glazing PYRO Pyroglasshield 20 minutes —Fire Protective
 Data Sheets
 For More
 Details

Group B: PPL (3/8") Pyran Platinum L up to 90 minutes—Fire Protective
> 1/4" Thickness CONTRA45 (1") 45 minute—Fire Protective
 See Glass CONTRA60 (1") 60 minutes—Fire Resistive
 Data Sheets CONTRA90 (1-1/2") 90 minutes Fire Resistive
 For More
 Details

Other Glazing Description: _____ **Glass Thickness:** _____"
 (INSU, BRG, LGShield, ARM, LAMI require separate submittal completed to select a specific model from available choices. Customer service will assist you in selecting the right vision frame for your specialty glazing)

STEP 2: Select Vision Lite Model

Vision Lites Group A Glazing: VSL* VLFEZ VLF VSLR VWL VLFR VLFSG
 (For 1-3/4" Doors Only)

Vision Lites Group B Glazing: VSIG VLFEZIG VLFIG VLFS10 VLFS10SP VWLIG
 Provide Door Thickness for all Models in this Group _____" (Frames are made to fit your glazing)
 (See product data for complete specifications for your vision frame including maximum door thickness)

STEP 3: Select Optional Finishes/Materials/Colors/Mullions

Optional Finishes & Materials: (S) Stainless Steel (G) Galvannealed (E) Zinc-Plated
 (See datasheet for product options. Not all models available in all finishes and materials)

Color Code (Steel Only): _____

VWL or VWLIG Wood Veneer Code: _____

Mullion Code: _____ Select Code from Mullion Submittals. Mullions provided for both sides.



STEP 4: Provide Size of Opening

Dimensions: Width: _____ **x Height:** _____


STEP 5: Glazing Tape/Packaging/Fasteners

Standard black PVC glazing tape for UL10B Doors **GTAPE200B**
 *VSL Frame Only for UL10C 20 Minute Wood Doors-UL Listed Black PVC glazing tape **GTAPE1/8**
 WS Glazing in sizes greater than 1296 square inches - **FGS3000S90** Glazing Tape.
 Add Intumescent glazing tape for all other UL10C Doors UL-Listed **FGS-4590**.
 Optional Intertek Warnock Hersey Label instead of UL (WS or PPF only)
Note: UL10C 20 minute wood doors requires FGS-4590 tape for Intertek listing.
 Torx Other Fasteners: _____
 Package Individually Bulk Packaging for Pallet Shipment

See detailed installation instructions to determine which tape is appropriate for the frame selected



Interpretation of Fire and Building codes May Vary. Consult with the Local Authority Having Jurisdiction (AHJ) to determine appropriate standards.

 AIR LOUVERS	Distributor:	Quantity:
	Architect:	Only 1 Model Per Page Please
	Contractor:	Version: 4/3/2023
	Project:	Date:
800-554-6077 QUOTES@ACTIVARCPG.COM ORDERS@ACTIVARCPG.COM SALES@ACTIVARCPG.COM © 2023 ACTIVAR CONSTRUCTION PRODUCTS GROUP INC MFG: COMMERCE CA, BLOOMINGTON MN • WAREHOUSES: SEE WEBSITE FOR LOCATIONS		