## VISION FRAME WITH 12 GAUGE SECURITY GRILLES: VLFSG™

## Security Vision Frame With Security Grille Each Side of Glass

## **SPECIFICATIONS:**

Material:	18 gauge CRS frame. Min size 4" x 4", Max 60" x 72". See Fire Rating Below.			
Grille:	12 gauge CRS with 13/16" square openings.			
Construction:	Mitered and welded corners, countersunk mounting holes both sides, security grille welded to frame.			
Powder Coat Finishes:	(B) Mineral Bronze (standard color) (BK) Black (FB) Flat Black (W) White (SB) SC Beige (SI) Silver (BA) Brass (S) Sand (AB) AMS Beige (G) Gray View Colors Online			
Door:	For 1-3/4" door. <b>Door cutout = order size.</b>			
Fasteners:	#8 x 32 Phillips head thru bolts with blank head one side to match finish.			
Glass:	3/16" - 1/4" glazing to be ordered separately from glazing submittals.  Visible light is 1" under rough opening size. Glass is 1/4" under order size.  Use fire rated glazing with Warnock Hersey or UL classification markings for fire rated applications.  Compatible Fire-Rated Air Louvers Glazing: WS, KERF, PPF			
Fire-Rating, Testing & Listings:	When installed in properly rated and approved door, ratings up to 90 minutes can be achieved, depending on the glazing used. See glazing ratings for max exposed area. Tested and Listed for UL 10C and Criteria of UBC 7-2 Positive Pressure. See detailed installation instructions.			

## **OPTIONS AT ADDITIONAL COST:**





UBC 7-2 Installation:	Additional intumescent tape for <b>Positive Pressure UL10C</b> .  See detailed installation instructions.			
Finishes & Materials:	(G) Galvanneal (E) Zinc Plated			
Fasteners:	Torx Other:			
Privacy Screen:	Add the Velo Privacy Screen to This Vision Lite—See Web Page for Details			
Custom:	PAK, leadlined or special orders—contact customer service.			

			VLF	SG		
		V-	<b>√</b>	· F		
► VISIBLE LITE = 1" UNDER ORDER SIZE	GLAZING SPACE IS GLASS THICKNESS			SECURITY GRILLE	GLASS SIZE IS 1/4" UNDER ORDER SIZE	ORDER SIZE = DOOR CUT OUT
1,1/4	4" \[			= <b>إ</b> ِ		<u> </u>
<u> </u>	_2	1~	1	الا <u>ر</u>		

Order	ormat: VLFSG					Example: VLFSG 1212 W
	-	Option G,E	W	Н	Color	

Interpretation of Fire and Building Codes May Vary. Consult with the Local Authority Having Jurisdiction (AHJ) to determine appropriate standards.

	Distributor:	Width:x Height:			
ACTIVAR A	Architect:	Quantity:			
CONSTRUCTION PRODUCTS GROUP INC.	Contractor:	Model:			
© 2021 Activar Construction Products Group, Inc.	Project:	Date: Version: 3/16/21			
800-554-6077 Quot	ES@ACTIVARCPG.COM ORDERS@ACTIVARCPG.COM	SALES@ACTIVARCPG.COM			
VISIT <u>www.activarcpg.com</u> for the most updated product information before ordering					
MFG: COMMERCE CA, BLOOMINGTON, MN • WAREHOUSES: SEE WEBSITE FOR LOCATIONS					